

| PF | Product Fiche according to (EU) No 65/2014 | | | |
|-----------|---|-----------------------------|--------------|--------------|
| S | Supplier's name or trade mark | PYRAMIS | | |
| M | Model identifier | CORSO cod. 065021701 | | |
| | Annual Energy Consumption | AEC hood | 116.8 | kWh/a |
| | Energy Efficiency Class | EEl class | C | |
| | Fluid Dynamic Efficiency | FDE hood | 15.6 | % |
| | Fluid Dynamic Efficiency class | FDE class | D | |
| | Light Efficiency | LE hood | 74.0 | lux/W |
| | Lighting Efficiency Class | LE class | A | |
| | Grease Filtering Efficiency | GFE hood | 80.7 | % |
| | Grease Filtering Efficiency class | GFE class | C | |
| | Minimum Air Flow in normal use | Q min | 348 | m³/h |
| | Maximum Air Flow in normal use | Q max | 467 | m³/h |
| | Air Flow at intensive/boost setting | Q boost | 704 | m³/h |
| | A-weighted Sound Power Emission at minimum speed | SPE min | 43 | dB(A) re 1pW |
| | A-weighted Sound Power Emission at maximum speed | SPE max | 60 | dB(A) re 1pW |
| | A-weighted Sound Power Emission at intensive or boost speed | SPE boost | 69 | dB(A) re 1pW |
| | Power consumption off mode | Po | 0.00 | W |
| | Power consumption in standby mode | Ps | 0.48 | W |

| Additional Information according to (EU) No 66/2014 | | | | |
|--|--|-----------------|--------------|------|
| | Time increase factor | f | 1.4 | |
| | Energy Efficiency Index | EEl hood | 83.5 | % |
| | Measured air flow rate at best efficiency point | Q bep | 391.0 | m³/h |
| | Measured air pressure at best efficiency point | P bep | 321 | Pa |
| | Maximum air flow | Q max | 704 | m³/h |
| | Measured electric power input at best efficiency point | W bep | 224.3 | W |
| | Nominal power of the lighting system | WL | 4.8 | W |
| | Average illumination of the lighting system on the cooking surface | E middle | 356 | lux |